

SPECIFICATIONS

■ Controller Box

Model	Description	
CS3000	Processor / Chip set	X86 soc
	Memory	Main memory: 128MB
	OS	Embedded Linux for POS
	BIOS	RSL POS BIOS V1.0
	I/O	1 x PS/2 Keyboard port 1 x PS/2 Mouse port 1 x Parallel: Supports SPP/EPP/ECP mode (internal) 4 x Serial: Com1, 2/COM3, 4 with 5/24V power selectable (9P D-sub, Male) 2 x USB: 12Mbps (Only available on Linux version) 1 x VGA: VESA 2.0 1 x LAN: 10/100 base-T
	POS Printer	Support UI or TM88 compatible
	HDD	2.5" or DOM
	Custom Display	1 Line LED or 3 Lines alphanumeric
	POS Keyboard	Programmable KB with 98 Keys/105 Keys/120 Keys
	Power Supply	Input: AC100V-230V, 50/60Hz 24V power outlet (Max. 3A) for printer drive
	MISC. IF	Touch, Slot scanner, MSR, EDC (Only available on Linux version)
	Monitor	CRT or LCD
	Dimensions	CPU BOX 203(W) x 106(D) x 55(H) mm

■ Printer

Model	Description
TM-U300	Epson Dot Matrix Printer with 1 line validation.
TM-U220D	Epson Dot Matrix Receipt Printer

■ POS Keyboard

Model	Description
PKB-80	Programmable 80 keys KB
PKB-105	Programmable 105 keys KB

■ Operator Display

Model	Description
CRT-9M	9" mono CRT
CRT-9C	9" color CRT
LCD-12	12" TFT LCD monitor

■ Cash Drawer

Model	Description
CBX-200	6P/24V 42(W) x 44(D) x 11(H)

Note: All brand and product names appearing in this brochure are trademarks, registered trademarks or service marks of their respective holders.



SEQUOIA SOLUTIONS SDN BHD

21-6, Block E1, Dataran Prima,
Jalan PJU 1/42,
47301 Petaling Jaya, Malaysia.
Tel: (603) 7880 9700 Fax: (603) 7880 4200
www.sequoia-asia.com

Distributed by: