

TSC TTP-243E

TTP-243E		
Introduction		Image
<ul style="list-style-type: none"> -Up to 512KB Flash memory and 2MB DRAM memory -Up to 76mm (3.0") per second print speed -Ribbon capacity up to 300m (984') -Label capacity up to 203mm OD (8.4" OD) -2-year warranty -Options include stand-alone printer controller, rotary cutter, and expandable flash memory cartridges. 		 <p style="text-align: center;">TSC TTP243E</p>
Specifications		
	TTP-243	TTP-243E
Printing Method	Thermal transfer and/or direct thermal	
Print Speed	38mm, 50mm, 76mm per second (1.5, 2.0, 3.0 ips)	
Resolution	203 dpi (8 dots/mm)	
Maximum Print Width	4.09"	
Print Length	1"-4.2"	
Maximum Print Length	90"	
Memory	1M FLASH ROM & 2M DRAM	512K FLASH ROM & 2M DRAM
Cutter	4" width rotary cutter (label thickness up to 0.20mm)	None
Communication Interfaces	RS232 and Centronics Parallel ports	
Dimension	232mm W x 288mm D x 156mm H (9.1" W x 11.3" D x 6.2" H)	
Bar Code	Code 39, Code 93, Code 128 UCC, Code 128 subsets A.B.C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 & 5 digits add-on PDF-417, Maxicode, DataMatrix	
Fonts	Five alphanumeric fonts 0, 90, 180, 270 degrees	
Maximum Ribbon Length	300M	
Maximum Ribbon Width	110mm	
Options & Accessories	Keyboard Display Unit (KP-200) Chinese, Japanese Kanji, and Korean font cards Flash memory expansion cartridge up to 4MB	