

# Zebra Z4MPlus



Form follows function in this simple-to-operate Z4Mplus™ die-cast metal thermal printer. Available in both 203 dpi (8 dots/mm) and 300 dpi (12 dots/mm), this dependable performer offers many standard features, including ZebraLink™ with Alert and WebView for centralized printer management. Rely on these top-of-the-line printers to get the job done, cost-effectively, with Zebra's faster linear PCMCIA Flash memory option that drives productivity farther than ever before!

Upgradeable to grow with changing needs, the Z4Mplus is ideal for shipping and receiving, compliance labeling, asset tracking, work in process, transportation and hospitality ticketing, and commercial or small business needs. With an internal Ethernet option, super-fast external memory options, industry leading throughput, and complex multi-language font support, the Z4Mplus is an unbeatable commercial printer.

## Standard Features

- Print methods: Thermal transfer or direct thermal
- ZebraLink (requires PSII to unleash Webview and Alert)
  - 32 bit processor
  - Transmissive/reflective media sensor
- Metal media cover with large clear window
  - Real time clock
  - Auto-calibration
  - Auto-ranging power supply
  - Color-coded operator cues
  - Back-lit LCD control panel
- RS-232 serial and bi-directional parallel interface
  - Zebra's E<sup>3</sup>® Printhead Energy Control

## Resolutions

Standard 203 dpi (8 dots/mm)

## Maximum Print Speeds

10" (254 mm/sec) (203 dpi)

6" (152 mm/sec) (300 dpi)

## Memory

Standard 8MB DRAM, 2 MB Flash

Optional:  
Up to 32 MB additional linear Flash (PCMCIA)  
Up to 256 MB additional ATA format (PCMCIA or CompactFlash cards)

**Physical Characteristics**

Width: 10.93"/278 mm  
Depth: 18.69"/475 mm  
Height: 13.32"/338 mm  
Weight (without packaging): 32.4 lbs/15 kg

**Communication Interface Capabilities**

RS-232C (422/485 with serial port adapter)  
Bi-directional IEEE 1284 parallel port  
Embedded ZebraLink Webview and Alert features (require optional ZebraNet PrintServer II)  
ZebraNet PrintServer II option (internal or external)

**Media Specifications**

Label and liner width: 1"/25.4 mm to 4.5"/114 mm  
Tear/Cutter  
Ribbon width: 1"/25.4 mm to 4.25"/108 mm  
Peel/Cutter  
Maximum non-continuous label length 39"/991 mm

**Maximum Print Area**

Width: 4.09"/104 mm  
Length with 203 dpi: 165"/4,202  
Length with 300 dpi (optional): 73"/1,869 mm

**Max. Roll Size**

8"/203 mm O.D. on a 3"/76 mm I.D. core

**Thickness (label & liner)**

.0023"/.058 mm to .01"/.25 mm